


**LHD 20X10**



MAT
Temperature: -5 - +60°C
Fire: 850°C
Flame: A1 - F
Time: 30 sec.
Energy: 0,5 J
Area: 140 mm<sup>2</sup>
Pb Free
Explosion: ⚡
IP: IP 40
IK: IK06

- ✓ Standard shape.
- ✓ Designed for wall or ceiling mounting.
- ✓ Double lock on lid increasing the trunking's rigidity and ensuring stronger cover fixation.

Accessories			
	conf.	package	EAN
<b>8921 - end</b>			
	HB	10	8595057619975
<b>8922 - connecting</b>			
	HB	10	8595057619982
<b>8923 - bending</b>			
	HB	10	8595057619999
<b>8924 - branching</b>			
	HB	10	8595057620001
<b>8925 - inner corner</b>			
	HB	10	8595057620018
<b>8926 - outer corner</b>			
	HB	10	8595057620025
<b>PNQ 20X10 - instrument carrier QUADRO</b>			
	HB	82	8595568927194
more information on pg. 2-60			

conf.		L			EAN	note
		m	m			
HA	white	3	90	folie	8595057620575	without protective foil
HD	white	2	96	carton	8595057620582	with protective foil
P2	white	2	96	carton	8595057691018	self-adhesive tape