


PK 170X70 D



- ✓ Designed for inserting power and communication circuits, security lines and other lines.
- ✓ Individual lines can be electromagnetically shielded by inserting a shielding canal, which is fixed to the trunking by clamps PSK 1.
- ✓ For traditional devices, which are installed in instrument box clamped in trunking bottom grooves.

conf.		L			EAN	note
		m	m			
HD	white	2	6	carton	8595057632943	

Accessories

	conf.	package	EAN
8441 - end			
	HB	2; 10	8595057628953
8442 - connecting			
	HB	2	8595057628960
8443 - bending			
	HB	2	8595057628977
8444 - branching			
	HB	2	8595057628984
8445 - inner corner			
	HB	2	8595057628991
8446 - outer corner			
	HB	2	8595057629004
8447 - grommet			
	HB	2	8595057655188
partition wall			
PEKE 60	-C	20 m	8595057627079
PKS 70/60	XX	20 m	8595057664364
PEP 60	HD	32 m	8595057668768
PEP 60/K	S	24 m	8595057668775
more information on pg. 2-57 - 2-58			
shielding canal			
SK 40X20	S	12 m	8595057614840
SK 40X33	S	12 m	8595057630291
more information on pg. 2-59			
instrument box, instrument carrier			
KP PK	HB	10	8595057629011
PN PK	S	1	8595057662377
more information on pg. 2-62			
instrument washer			
8440-11	HB	10	8595057644052
8440-12	HB	10	8595057644069
8440-13	HB	10	8595057644076
more information on pg. 2-63			

MAT material

fire reaction class of underlying material

temperature resistance

flaming loop test

self-snuffing

impact strength

inside area

for mounting and double-socket

for mounting a wall socket

leadless material

IP protection

mechanical protection

color

package